June 14, 2016

DRAFT

Explanatory Report for the Proposed Desired Future Conditions

of the Western Fresh Edwards (Balcones Fault Zone) Aquifer

Groundwater Management Area 10

Sect	ion	•••••		Page				
APP	PENDIC	ES		iv				
FIG	URES	•••••		V				
TAE	BLES	•••••		vi				
1.	Grou	ındwater N	Management Area 10	1				
2.	Aqui	Aquifer Description1						
3.	Desi	red Future	Conditions	2				
4.	Polic	y Justifica	tion	3				
5.	Tech	nical Justi	fication	3				
6.	Cons	sideration	of Designated Factors	5				
••	6.1	Aquifer	Uses or Conditions	6				
		6.1.1	Description of Factors in the Western Fresh Edwards					
		01111	(Balcones Fault Zone) Aquifer in Kinney County	6				
		6.1.2	DFC Considerations	6				
	6.2	2 Water-Supply Needs						
		6.2.1	Description of Factors in the Western Fresh Edwards					
			(Balcones Fault Zone) Aquifer in Kinney County	6				
		6.2.2	DFC Considerations	7				
	6.3	Water-N	Management Strategies	8				
		6.3.1	Description of Factors in the Western Fresh Edwards					
			(Balcones Fault Zone) Aquifer in Kinney County	8				
		6.3.2	DFC Considerations	9				
	6.4	Hydrolo	ogical Conditions	10				
		6.4.1	Description of Factors in the Western Fresh Edwards					
			(Balcones Fault Zone) Aquifer in Kinney County	10				
		6.4.1.1	Total Estimated Recoverable Storage	10				
		6.4.1.2	Average Annual Recharge	10				
		6.4.1.3	Inflows	11				
		6.4.1.4	Discharge	11				
		6.4.1.5	Other Environmental Impacts Including Springflow and					
			Groundwater/Surface Water Interaction	12				
		6.4.2	DFC Considerations	12				
7.	Subs	idence Im	pacts	12				
8.	Socio	oeconomic	Impacts Reasonably Expected to Occur	12				

Table of Contents

	8.1	Description of Factors in the Western Fresh Edwards (Balcones	
		Fault Zone) Aquifer in Kinney County	12
	8.2	DFC Considerations	13
9.	Priva	ate Property Impacts	13
	9.1	Description of Factors in the Western Fresh Edwards (Balcones	
		Fault Zone) Aquifer in Kinney County	13
	9.2	DFC Considerations	
10.	Feas	ibility of Achieving the DFCs	14
11.	Discu	ussion of Other DFCs Considered	14
12.	Discu	ussion of Other Recommendations	14
	12.1	Advisory Committees	14
	12.2	Public Comments	14
13.	Any	Other Information Relevant to the Specific DFCs	14
14.	Prov	ide a Balance Between the Highest Practicable Level of Groundwater	
	Prod	luction and the Conservation, Preservation, Protection, Recharging, and	
	Prev	ention of Waste of Groundwater and Control of Subsidence in the Mana	gement
	Area		14
15.	Refe	rences	15

List of Appendices

Appendix A—Proposed Desired Future Condition Resolution

Appendix B—Texas Water Development Board GAM Task xxxx (Revised): Total Estimated Recoverable Storage for Aquifers in GMA 10

Appendix C—Socioeconomic Impacts Analyses for Regions K, L, and M

FIGURES

Figure	e Page
1	Map of the administrative boundaries of GMA 10 and Groundwater Conservation Districts in GMA (From TWDB website)
2	Discharge at Las Moras Springs (cfs) (red line) compared to water levels in the Well No. 70-38- 902 (ft, mean sea level) (blue line). Spring discharge data are taken from the U.S. Geological Survey. Water elevation data are taken from the TWDB

TABLES

Table	Page
1	DFCs for the western fresh Edwards (Balcones Fault Zone) Aquifer in GMA 103
2	MAG for the Edwards (Balcones Fault Zone) Aquifer in GMA 10 in Kinney County. Results are in acre-ft/yr and designated by river basin (Kinney County GCD, 2013)5
3	Estimated historical water use. TWDB historical water use survey data (Allen, 2013) (acre-ft/yr)6
4	Projected water demands. TWDB 2012 State Water Plan data (Allen, 2013) (acre-ft/yr)7
5	Projected water supply needs. TWDB 2012 State Water Plan data (Allen, 2013) (acre-ft/yr)7
6	Projected water-supply shortages in Kinney County under drought –of-record conditions based on no new infrastructure development (Plateau Region Water Planning Group, 2015) (acre-ft/yr)
7	Source water available after known demands are subtracted (Plateau Region Water Planning Group, 2015) (acre-ft/yr)
8	Water-use categories where no water supply is available to meet its total need. These data are not currently available in the Plateau Region Water Planning Group Plan (Plateau Region Water Planning Group, 2015) (acre-ft/yr)
9	Recommended and alternative water-management strategies that if implemented may assist in meeting supply shortages (Plateau Region Water Planning Group, 2015)
10	Total estimated recoverable storage for the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer within Kinney County. Estimates are rounded within two significant numbers (Jones et al., 2013)
11	Summarized information for the Edwards (Balcones Fault Zone) Aquifer that is needed for Kinney Count GCD's Groundwater Management Plan. All values are approximate and reported in acre-ft/yr (Hutchison et al., 2011)

Abbreviations

DFC	Desired Future Conditions
GCD	Groundwater Conservation District
GMA	Groundwater Management Area

- MAG Modeled Available Groundwater
- TWDB Texas Water Development Board

1. Groundwater Management Area 10

Groundwater Management Areas (GMA) were created by the Texas Legislature to provide for the conservation, preservation, protection, recharging, and prevention of waste of the groundwater, and of groundwater reservoirs or their subdivisions, and to control subsidence caused by withdrawal of water from those groundwater reservoirs or their subdivisions. Each GMA is charged with facilitating joint planning efforts in the GMAs within its jurisdiction.

GMA 10 was created to oversee the Edwards (Balcones Fault Zone) and Trinity aquifers. Other aquifers include the Leona Gravel, Buda Limestone, Austin Chalk, and the saline Edwards (Balcones Fault Zone) aquifers. The jurisdiction of GMA 10 includes all or parts of Bexar, Caldwell, Comal, Guadalupe, Hays, Kinney, Medina, Travis, and Uvalde counties. GCDs in GMA 10 include Barton Springs/Edwards Aquifer Conservation District, Comal Trinity GCD, Edwards Aquifer Authority, Kinney County GCD, Medina County GCD, Plum Creek Conservation District, and Uvalde County Underground Water Conservation District (UWCD) (Figure 1).

As mandated in Texas Water Code § 36.108, districts are required to submit DFCs of the groundwater resources in their GMA to the executive administrator of the Texas Water Development Board (TWDB), unless that aquifer is deemed to be non-relevant. According to Texas Water Code § 36.108 (d-3), the district representatives shall produce a DFCs Explanatory Report for the management area and submit to the TWDB a copy of the Explanatory Report.

The fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer located within Kinney County is a major aquifer. The extent of this aquifer includes the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer located within Kinney County (Figure 1). This document is the Explanatory Report for the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer located within Kinney County.

2. Aquifer Description

For jurisdicational purposes, the fresh-water portion of the San Antonio segment of the Edwards (Balcones Fault Zone) Aquifer is defined as the fresh water portion of the Edwards (Balcones Fault Zone) Aquifer located within Kinney County. The boundaries of the western fresh-water Edwards (Balcones Fault Zone) Aquifer were determined using the Digital Geologic Atlas of Texas (U.S. Geological Survey, 2005; Stoeser et al., 2005) and the GMA 10 boundary. The geographic extent of the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer located within Kinney County is available at the TWDB website

http://www.twdb.texas.gov/groundwater/models/gam/ebfz_s/ebfz_s.asp (Figure 2). As illustrated, the jurisdiction is limited to the eastern portion of Kinney County. The western freshwater portion of the Edwards (Balcones Fault Zone) Aquifer is located entirely within the Regional Water Planning Area J and the Kinney County GCD. The geographic extent of the western fresh-water Edwards (Balcones Fault Zone) Aquifer in the Kinney County GCD is illustrated in Figures 1 and 2.



Figure 1. Map of the administrative boundaries of GMA 10 and GCDs in GMA (From TWDB website)

3. Desired Future Conditions

GMA 10 incorporated information from the Kinney County GCD Groundwater Management Plan and analyses from the TWDB during development of the proposed DFCs. The first cycle of the Desired Future Condition for the western fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County in GMA 10 was that the water level in well 70-38-902 shall not fall below 1,184 ft mean sea level (Table 1). This Desired Future Condition was described in Resolution No. 2010-11 and adopted August 23, 2010 by the GCDs in GMA 10.

The second cycle of the Desired Future Condition for the western fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County in GMA 10 remained the same as during the first cycle of DFCs, that the water level in well 70-38-902 shall not fall below 1,184 ft mean sea level (Table 1). The second cycle of the DFCs was adopted by the GCDs in GMA 10 on March 14, 2016 as Resolution No. 2016-xx (Appendix A).

Aquifer	Desired Future Condition Summary	Date Desired Future Condition Adopted
Edwards (Kinney County)	Water level in well number 70-38-902 shall not fall below 1,184 feet mean sea level	8/4/2010
Edwards (Kinney County)	Water level in well number 70-38-902 shall not fall below 1,184 feet mean sea level	?/?/2015

Table 1. DFCs for the western fresh Edwards (Balcones Fault Zone) Aquifer in GMA 10

4. Policy Justification

The Desired Future Condition for the San Antonio segment of the fresh-water Edwards (Balcones Fault Zone) Aquifer in Kinney County was adopted after considering factors identified in Texas Water Code §36.108 (d):

- 1. Aquifer uses or conditions within the management area, including conditions that differ substantially from one geographic area to another;
 - a. for each aquifer, subdivision of an aquifer, or geologic strata and
 - b. or each geographic area overlying an aquifer
- 2. The water supply needs and water management strategies included in the state water plan;
- 3. Hydrological conditions, including for each aquifer in the management area the total estimated recoverable storage as provided by the executive administrator, and the average annual recharge, inflows, and discharge;
- 4. Other environmental impacts, including impacts on spring flow and other interactions between groundwater and surface water;
- 5. The impact on subsidence;
- 6. Socioeconomic impacts reasonably expected to occur;
- 7. The impact on the interests and rights in private property, including ownership and the rights of management area landowners and their lessees and assigns in groundwater as recognized under Section 36.002;
- 8. The feasibility of achieving the desired future condition; and,
- 9. Any other information relevant to the specific DFCs.

These factors are discussed in detail in appropriate sections in this Explanatory Report.

5. Technical Justification

Technical justification for selection of the Desired Future Condition for the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer in Kinney County was provided by simulations generated by a groundwater flow model developed for the Edwards (Balcones Fault Zone) Aquifer in Kinney County (Hutchison et al., 2011). The Kinney County groundwater model was developed by Hutchison et al. (2011) for use in management plan data analysis. The model was calibrated to water-level and spring discharge data collected from 1950 to 2005; however, data were extracted only for the period from 1980 to 2005 for the Kinney County GCD Groundwater Management Plan (Kinney County GCD Groundwater Management Plan, 2013). These dates were used to avoid skewing the data as a result of the drought of the 1950s. The period from 1980 to 2005 includes both drought and wet climatic conditions.

Kinney County has two DFCs, one for GMA 7, which includes the western half of Kinney County, and one for GMA 10, which includes the eastern half of Kinney County. The two DFCs for Kinney County are separate, but both were specified for the same intent, to protect flow at Las Moras Springs. GMA 7, which includes western Kinney County and Las Moras Springs, designated as its Desired Future Condition that drawdown for the Edwards-Trinity Aquifer in western Kinney County be consistent with maintaining flow at Las Moras Springs at an annual average flow of 23.9 cfs and a median flow of 24.4 cfs. GMA 10, which does not include Las Moras Springs, used the Kinney County groundwater flow model developed by Hutchison et al. (2011) to specify as its Desired Future Condition that the water level at Well No. 70-38-902 be maintained at or above an elevation of 1,184 feet msl.

These two DFCs are essentially synonymous because Las Moras Springs discharge is well correlated with groundwater elevation at Well No. 70-38-902 (Figure 2). The Desired Future Condition of 1,184 ft msl at Well No. 70-38-902 was chosen by GMA 10 based on an assessment by TWDB that correlated groundwater elevation of 1,184 ft msl at Well No. 70-38-902 to discharge of approximately 24 cfs at Las Moras Springs (Figure 3). Well No. 70-38-902 is alternatively identified as the Tularosa Well or the Tularosa Monitoring Well.

The DFCs for Kinney County were chosen to protect Las Moras Springs. The GMA Desired Future Condition of an annual average flow of 23.9 cfs and a median flow of 24.4 cfs discharge from the Las Moras Springs was chosen to represent pre-development conditions when the springs did not go dry, or at least did not go dry as often as they did during the period during which the number of irrigated acres were greatest. The GMA 10 Desired Future Condition which specifies that the water level at Well No. 70-38-902 be maintained at or above an elevation of 1,184 ft msl was chosen for the same reasoning. The elevation of 1,184 ft msl has been determined to correlate directly with Las Moras Springs discharge rate of 24.4 cfs.

The Modeled Available Groundwater (MAG) for the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer was calculated by the TWDB (Shi et al., 2012) and provided in GAM Run 12-002 MAG (Shi, 2012). The new model run is identified as an update of Scenario 3 of Groundwater Availability Modeling (revised) Task 10-027 (Hutchison, 2011). The model runs were based on the MODFLOW-2000 model developed by the TWDB to assist with the joint planning process regarding the Kinney County GCD (Hutchison et al., 2011). In both model runs, the total pumping in Kinney County was maintained at approximately 77,000 acre-feet per year to achieve the Desired Future Condition. The MAG for the GMA 10 portion of Kinney



County is 6,321 acre-ft/yr (Table 2). Details regarding this model run are summarized in Shi et al. (2012).

Figure 2. Discharge at Las Moras Springs (cfs) (red line) compared to water levels in the Well No. 70-38-902 (ft, mean sea level) (blue line). Spring discharge data are taken from the U.S. Geological Survey. Water elevation data are taken from the TWDB.

Divor Pogin		Year						
Kiver Dasiii	2010	2020	2030	2040	2050	2060		
Nueces	6,319	6,319	6,319	6,319	6,319	6,319		
Rio Grande	2	2	2	2	2	2		
Total	6,321	6,321	6,321	6,321	6,321	6,321		

Table 2. MAG for the Edwards (Balcones Fault Zone) Aquifer in GMA 10 in Kinney County. Results are in acre-ft/yr and designated by river basin (Kinney County GCD, 2013).

6. Consideration of Designated Factors

According to Texas Water Code § 36.108 (d-3), the district representatives shall produce a Desired Future Condition Explanatory Report. The report must include documentation of how factors identified in Texas Water Code §36.108 (d) were considered prior to proposing a Desired Future Condition, and how the proposed Desired Future Condition impacts each factor. The following sections of the Explanatory Report summarize the information that Kinney County GCD used in its deliberations and discussions.

6.1 Aquifer Uses or Conditions

6.1.1 Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

The information in this section was prepared by the Groundwater Technical Assistance Section of the Groundwater Resources Division at the TWDB (Allen, 2013). This information is also included as an appendix in the Kinney County Conservation District Groundwater Management Plan (Kinney County Conservation District, 2013). Groundwater use within the Kinney County Conservation District is comprised primarily of pumpage and use from the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer with a much smaller component of pumpage coming from the Trinity Aquifer. The estimated historical surface-water and groundwater use in Kinney County for the period 2006-2007 is presented in Table 3.

(·] =) •							
Year	Source	Municipal	Manu- facturing	Steam Electric	Irrigation	Mining	Live- stock	Total
2006	GW	1,126	0	0	4,776	0	238	6,410
2006	SW	0	0	0	0	0	60	60
2007	GW	906	0	0	1,641	0	217	2,764
2007	SW	0	0	0	0	0	55	55
2008	GW	1,101	0	0	2,043	0	294	2,438
2008	SW	0	0	0	0	0	73	73
2000	GW	1,164	0	0	895	0	338	2,397
2009	SW	0	0	0	0	0	84	84
2010	GW	1,026	0	0	1,258	0	184	2,468
	SW	0	0	0	0	0	46	46

Table 3. Estimated historical water use. TWDB historical water use survey data (Allen, 2013) (acre-ft/yr).

6.1.2 DFC Considerations

The dominant use of the aquifer by pumping is public water supply, and the sustainability of that supply, especially for users who have no alternative supply physically or economically available and/or who are in vulnerable locations, must be protected to the extent feasible (Texas Water Code §36). The primary concern with sustainability of this karst aquifer groundwater supply is drought, notably extreme drought that stresses the entire aquifer. The DFCs supports and is, in fact, the linchpin of a drought-management program to promote long-term sustainability of both springflow and water supplies.

6.2 Water-Supply Needs

6.2.1 Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

The information in this section was prepared by the Groundwater Technical Assistance Section of the Groundwater Resources Division at the TWDB (Allen, 2013). This information is also

included as an appendix in the Kinney County Conservation District Groundwater Management Plan (Kinney County Conservation District, 2013). The TWDB provides water-supply needs estimates by decade as well as by water-user group basin. There are two major basins in Kinney Count; the Nueces River basin and the Rio Grande basin. Summaries of the projected water-supply demands and needs in acre-ft/yr are provided by decade in the Table 4 and 5 for each water-user group and each water-user group basin. As illustrated, the projected water-supply demands and needs are greater than the estimated historical water use for the years 2006-2010 (Table 3).

WUG WUG Basin		2010	2020	2030	2040	2050	2060
Irrigation	Nueces	338	323	310	296	284	271
Livestock	Nueces	187	187	187	187	187	187
County-other	Nueces	35	21	13	8	4	3
Brackettville	Rio Grande	583	583	582	582	581	582
County-other	Rio Grande	32	31	31	31	31	31
Irrigation	Rio Grande	13,169	12,605	12,063	11,547	11,053	10,582
Live Stock	Rio Grande	258	258	258	258	258	258
Fort Clark Springs MUD	Rio Grande	626	653	678	704	723	727
Sum of Projected W	15,228	14,661	14,122	13,613	13,121	12,641	

Table 4 Projected water demands. TWDB 2012 State Water Plan data (Allen, 2013) (acre-ft/yr)

Table 5.	Projected water suppl	y needs. TWD	B 2012 State	Water Plan	data (Allen, 201	3) (acre-
ft/yr).						

WUG	WUG Basin	2010	2020	2030	2040	2050	2060
Irrigation	Nueces	4,044	4,059	4,072	4,086	4,098	4,111
Livestock	Nueces	147	147	147	147	147	147
County-other	Nueces	13	27	35	40	44	45
Brackettville	Rio Grande	64	64	65	65	66	65
County-other	Rio Grande	56	57	57	57	57	57
Irrigation	Rio Grande	12,615	13,179	13,721	14,237	14,731	15,202
Livestock	Rio Grande	83	83	83	83	83	83
Fort Clark Springs Mud	Rio Grande	494	467	442	416	397	393
Sum of Projected Wa	17,516	18,083	18,622	19,131	19,623	20,103	

6.2.2 DFC Considerations

The dominant use of the Edwards (Balcones Fault Zone) Aquifer within the Kinney County GCD in GMA 10 by pumping is domestic use and irrigation, and the sustainability of that supply, especially for users who have no alternative supply physically or economically available and/or who are in vulnerable locations, must be protected to the extent feasible (Texas Water Code §36). The primary concern with sustainability of this karst aquifer groundwater supply is drought, notably extreme drought that stresses both aquifers. The DFC supports and is, in fact, the primary concern with sustainability of this karst aquifer groundwater supply is drought, notably extreme drought that stresses both aquifers. The DFC supports and is, in fact, the

linchpin of a drought management program to promote long-term sustainability of water supplies.

6.3 Water-Management Strategies

6.3.1 Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

The following information is from the Plateau Region Initially Prepared Water Plan (Plateau Region Water Planning Group, 2015). A major component of the Plateau Region Initially Prepared Water Plan is to identify municipalities and water-use categories that may, in times of severe drought, be unable to meet expected water-supply needs based on today's ability to access, treat, and distribute the supply. A goal of the Plateau Region Initially Prepared Water Plan is to provide for the health, safety, and welfare of the human community, with as little detrimental effect to the environment as possible. Recreation activities involve human interaction with the outdoor environment and are often directly dependent on water resources. It is recognized that the maintenance of the regional environmental community's water supply needs serves to enhance the lives of citizens of the Plateau Region as well as the tens of thousands of annual visitors to this Region. The implementation of water-management strategies recommended in the Plateau Region Initially Prepared Water Plan is not expected to have any impact on native-water quality. In particular, primary and secondary safe drinking water standards, which are the key parameters of water quality identified by the Plateau Region Water Planning Group as important to the use of the water resource, are not compromised by the implementation of the strategies. Also, no recommended strategies involve moving water from a rural location for use in an urban area.

The data presented in this section are provided by the Plateau Region Water Planning Group Plan (Plateau Region Water Planning Group, 2015). Recommended alternatives, or watermanagement strategies, to meet anticipated drought-induced shortages are presented in the Plateau Region Initially Prepared Water Plan for consideration. Table 6 lists the projected water supply shortages in Kinney County under drought-of-record conditions based on no new infrastructure development. Table 7 lists source water available after known demands are subtracted. Table 8 identifies water-use categories where no water supply is available to meet its total need. As noted, these data are not currently available in the Plateau Region Water Planning Group Plan. Table 9 provides a listing of all recommended and alternative water management strategies in the Plateau Region Water Planning Group Plan that if implemented may assist in meeting supply shortages.

Table 6. Projected water-supply shortages in Kinney County under drought –of-record conditions based on no new infrastructure development (Plateau Region Water Planning Group, 2015) (acre-ft/yr)

WUG/WWP	Basin	2020	2030	2040	2050	2060	2070
Livestock	Rio Grande	22	22	22	22	22	22

Groundwater	Basin	Salinity	2020	2030	2040	2050	2060	2070
Austin Chalk	Rio	Brackish	4 045	4.045	4.045	4.045	4.045	4.045
Aquifer	Grande	Diackish	4,045	4,045	4,045	4,043	4,045	4,043
Edwards								
(Balcones	Nueses	Erach	2 121	2 121	2 1 2 1	2 121	2 121	2 121
Fault Zone)	Indeces	riesii	5.454	3.434	5.454	3.434	5.454	5.454
Aquifer								
Edwards								
(Balcones	Rio	Frach	2	2	2	2	2	2
Fault Zone)	Grande	TIESH	Z		2	Ζ.	2	2
Aquifer								

 Table 7. Source water available after known demands are subtracted (Plateau Region Water Planning Group, 2015) (acre-ft/yr)

Table 8. Water-use categories where no water supply is available to meet its total need. These data are not currently available in the Plateau Region Water Planning Group Plan (Plateau Region Water Planning Group, 2015) (acre-ft/yr)

WUG/WWP	Basin	2020	2030	2040	2050	2060	2070
-	-	-	-	-	-	-	

Table 9.	Recommended and alternative water-management strategies that if implemented may	r
assist in	eeting supply shortages (Plateau Region Water Planning Group, 2015)	

Water	Water	S	strategy	Supply	(acre-f	ft/yr)		Total
Utility	Management	2020	2030	2040	2050	2060	2070	Capital
Group	Strategy							Cost
City of	Conservation:	58	58	58	58	58	58	\$1,116
Brackettville	Water loss audit and							
	main-line repair							
	Increase supply to	3	3	3	3	3	3	\$751,000
	Spoford with new							
	water line							
	Increase storage	3	3	3	3	3	3	\$288,000
	facility							
Ft Clark	Increase storage	620	620	620	620	620	620	\$1,033,000
Springs	facility							
MUD								
Kinney	Conservation:	145	145	145	145	145	145	\$0
County	Vegetative							
Other	management _							
	Arundo donax							
Kinney	Additional water	20	20	20	20	20	20	\$55,000
County	wells							
Livestock								

6.3.2 DFC Considerations

The DFC under consideration here is specific to the Edwards (Balcones Fault Zone) Aquifer within the Kinney County GCD in GMA 10. The DFC for the Edwards (Balcones Fault Zone) Aquifer within the Kinney County GCD in GMA 10, as described above, underpins an aquifer-responsive drought management program that encourages both full-time water conservation and further temporary curtailments in pumping during drought periods that increase with drought severity.

6.4 Hydrological Conditions

6.4.1 Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

6.4.1.1 Total Estimated Recoverable Storage

Texas statute requires that the total estimated recoverable storage of relevant aquifers be determined. Total estimated recoverable storage is a calculation provided by the TWDB. Texas Administrative Code Rule §356.10 (Texas Administrative Code, 2011) defines the total estimated recoverable storage as the estimated amount of groundwater within an aquifer that accounts for recovery scenarios that range between 25 percent and 75 percent of the porosity-adjusted aquifer volume. As described in GAM Task 13-033 (Jones et al., 2013), the total recoverable storage estimated for the Edwards (Balcones Fault Zone) Aquifer within the Kinney County GCD in GMA 10 is listed in Table 10. Total estimated recoverable storage values may include a mixture of water-quality types, including fresh, brackish, and saline groundwater, because the available data and the existing Groundwater Availability Models do not permit the differentiation between different water-quality types. The total estimated recoverable storage values do not take into account the effects of land surface subsidence, degradation of water quality, or any changes to surface-water/groundwater interaction that may occur due to pumping.

Table 10. Total estimated recoverable storage for the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer within Kinney County. Estimates are rounded within two significant numbers (Jones et al., 2013).

Total Storage	25 percent of Total Storage	75 percent of Total Storage
(acre-ft)	(acre-ft)	(acre-ft)
3,100,000	775,000	2,325,000

6.4.1.2 Average Annual Recharge

Shi and Wade (2013) calculated the average annual recharge of the Edwards (Balcones Fault Zone) Aquifer in Kinney County using the Kinney County alternative Groundwater Availability Model (Hutchison et al., 2011). The alternative Groundwater Availability Model encompassed all of Kinney County, thus the analysis included both GMAs 7 and 10 in Kinney County. As presented in Table 11, recharge to the Edwards (Balcones Fault Zone) Aquifer in Kinney County was calculated to be 17,674 acre-ft/yr.

Table 11. Summarized information for the Edwards (Balcones Fault Zone) Aquifer that is needed for Kinney Count GCD's Groundwater Management Plan. All values are approximate and reported in acre-ft/yr (Hutchison et al., 2011).

Management Plan requirement	Aquifer and other units	TWDB Kinney GCD Model (1980 – 2005)	
Estimated annual amount of recharge from precipitation to the district	Edwards (Balcones Fault Zone) Aquifer	17,674	
Estimated annual volume of water that discharges from the aquifer to springs and any surface water body including lakes, streams, and rivers	Edwards (Balcones Fault Zone) Aquifer	514	
Estimated annual volume of flow into the district within each aquifer in the district	Edwards (Balcones Fault Zone) Aquifer	268	
Estimated annual volume of flow out of the district within each aquifer in the district	Edwards (Balcones Fault Zone) Aquifer	12,346	
	From Upper Cretaceous Units to Edwards (Balcones Fault Zone) Aquifer	15,597	
Estimated net annual volume of flow between each aquifer in the district	From Edwards-Trinity (Plateau) Aquifer to Edwards (Balcones Fault Zone) Aquifer	11,514	
	From Edwards (Balcones Fault Zone) Aquifer to Edwards-Trinity Units	33,598	

6.4.1.3 Inflows

Shi and Wade (2013) calculated inflows to the Edwards (Balcones Fault Zone) Aquifer in Kinney County using the Kinney County alternative Groundwater Availability Model (Hutchison et al., 2011). The alternative Groundwater Availability Model encompassed all of Kinney County, thus the analysis included both GMAs 7 and 10 in Kinney County. As presented in Table 5, inflows to the Edwards (Balcones Fault Zone) Aquifer in Kinney County were calculated to be 268 acre-ft/yr.

6.4.1.4 Discharge

Shi and Wade (2013) calculated inflows to the Edwards (Balcones Fault Zone) Aquifer in Kinney County using the Kinney County alternative Groundwater Availability Model (Hutchison et al., 2011). The alternative Groundwater Availability Model encompassed all of Kinney County, thus the analysis included both GMAs 7 and 10 in Kinney County. As presented in Table 5, the estimated annual volume of water that discharges from the aquifer to springs and any surface water body including lakes, streams, and rivers from the Edwards (Balcones Fault Zone) Aquifer in Kinney County was calculated to be 514 acre-ft/yr. the estimated annual volume of flow out of the district within each aquifer in the district from the Edwards (Balcones Fault Zone) Aquifer in Kinney County was calculated to be 12,346 acre-ft/yr.

6.4.1.5 Other Environmental Impacts Including Springflow and Groundwater/Surface-Water Interaction

Shi and Wade (2013) calculated inflows to the Edwards (Balcones Fault Zone) Aquifer in Kinney County using the Kinney County alternative Groundwater Availability Model (Hutchison et al., 2011). The alternative Groundwater Availability Model encompassed all of Kinney County, thus the analysis included both GMAs 7 and 10 in Kinney County. As presented in Table 5, the net annual volume of flow between each aquifer in the district the Edwards (Balcones Fault Zone) Aquifer in Kinney County was calculated to be: (i) 15,597 acre-ft/yr from Upper Cretaceous Units to Edwards (Balcones Fault Zone) Aquifer; (ii) 11,514 acre-ft/yr from Edwards-Trinity (Plateau) Aquifer to Edwards (Balcones Fault Zone) Aquifer; and (iii) 33,598 acre-ft/yr from Edwards (Balcones Fault Zone) Aquifer to Edwards-Trinity Units.

6.4.2 DFC Considerations

The DFC is proposed on the basis that Edwards (Balcones Fault Zone) Aquifer in Kinney County is hydrologically a classic karst aquifer, with temporally variable inflows from various recharge sources and major natural discharge points at Las Moras, Pinto, and Mud springs that are also temporally variable with aquifer conditions. This hydrologic condition denotes that it is highly vulnerable to drought, and water supplies are substantially adversely affected by drought. Additionally, the geologic strata that form the aquifer dip regionally to the south, such that both the saturated thickness in the unconfined zone and the artesian pressure head in the confined zone are larger to the south. However, while faulted, the aquifer is well-integrated hydrologically and has a common potentiometric surface throughout the subdivision.

Springflows at Las Moras, Pinto, and Mud springs are directly and essentially solely related to the elevation of the potentiometric surface, regardless of the different thickness and depth of groundwater that exists in various parts of the subdivision or other hydrologic conditions, except as they affect the potentiometric surface. Preservation of minimal springflows at Las Moras, Pinto, and Mud springs are expressly designed to provide that level of environmental and ecological protection.

7. Subsidence Impacts

Subsidence has historically not been an issue with the Edwards (Balcones Fault Zone) Aquifer in Kinney County in GMA 10.

8. Socioeconomic Impacts Reasonably Expected to Occur

8.1. Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

Administrative rules require that regional water planning groups evaluate the impacts of not meeting water needs as part of the regional water planning process, and rules direct TWDB staff to provide technical assistance [§357.7 (4)(A)]. Staff of the TWDB's Water Resources Planning Division designed and conducted a report in support of the Plateau Region Water Planning Group (Region J). The report "Socioeconomic Impacts of Projected Water Shortages for the Plateau Region Water Planning Area (Region J)" was prepared by the TWDB in support of the 2011 Plateau Region Water Plan.

The report on socioeconomic impacts summarizes the results of the TWDB analysis and discusses the methodology used to generate the results for Region J. The socioeconomic impact report for Water Planning Group L is included in Appendix C.

8.2. DFC Considerations

Because none of the water-management strategies involve changes in the current use of the western fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County, as described in Section 6.3, the proposed DFCs do not have a differential socioeconomic impact. They are supportive of the status quo in this regard, which is considered positive.

9. Private Property Impacts

9.1 Description of Factors in the Western Fresh Edwards (Balcones Fault Zone) Aquifer in Kinney County

The impact on the interests and rights in private property, including ownership and the rights of GMA landowners and their lessees and assigns in groundwater is recognized under Texas Water Code Section 36.002. The legislature recognizes that a landowner owns the groundwater below the surface of the landowner's land as real property. Nothing in this code shall be construed as granting the authority to deprive or divest a landowner, including a landowner's lessees, heirs, or assigns, of the groundwater ownership and rights described by this section.

Texas Water Code Section 36.002 does not: (1) prohibit a district from limiting or prohibiting the drilling of a well by a landowner for failure or inability to comply with minimum well spacing or tract size requirements adopted by the district; (2) affect the ability of a district to regulate groundwater production as authorized under Section 36.113, 36.116, or 36.122 or otherwise under this chapter or a special law governing a district; or (3) require that a rule adopted by a district allocate to each landowner a proportionate share of available groundwater for production from the aquifer based on the number of acres owned by the landowner.

9.2 DFC Considerations

The DFC is designed to protect the sustained use of the aquifer as a water supply for all users in aggregate. The DFC does not prevent use of the groundwater by landowners either now or in the future, although ultimately total use of the groundwater in the aquifer is restricted by the aquifer

condition, and that may affect the amount of water that any one landowner could use, either at particular times or all of the time.

10. Feasibility of Achieving the DFCs

The feasibility of achieving a Desired Future Condition directly relates to the ability of the Kinney County GCD and GMA 10 to manage the fresh-water portion of the Edwards (Balcones Fault Zone) Aquifer in Kinney County to achieve the DFCs. The feasibility of achieving this goal is limited by the finite nature of the resource and how it responds to drought and the pressures placed on this resource by economic and population growth within the area served by this resource and the potential that water is exported out of the Kinney County GCD. Texas State law provides GCDs and GMAs with the responsibility and authority to conserve, preserve, and protect these resources and to insure for the recharge and prevention of waste of groundwater and control of subsidence in the management area. The feasibility of achieving these goals could be altered if state law is revised or interpreted differently than is currently the case.

11. Discussion of Other DFCs Considered

No other Desired Future Condition of the western fresh Edwards (Balcones Fault Zone) Aquifer was considered.

12. Discussion of Other Recommendations

12.1 Advisory Committees

An Advisory Committee for GMA 10 has not been established.

12.2 Public Comments

Each GCD must hold a public meeting within 90 days after the GMA approves its DFCs. During this meeting, the GCD needs to document stakeholder input. This input is to be submitted by a report from the GCD to the GMA within 90 days after the GMA approves its Desired Future Condition.

The Kinney County Groundwater Management District has not yet approved its DFCs. The Kinney County GCD has not yet held public meetings to gather public comment on the DFCs. No public comments have yet been offered regarding the Desired Future Condition for the freshwater portion of the Edwards (Balcones Fault Zone) Aquifer in Kinney County.

13. Any Other Information Relevant to the Specific DFCs

No additional information relevant to the specific DFCs has been identified.

14. Provide a Balance Between the Highest Practicable Level of Groundwater Production and the Conservation, Preservation, Protection, Recharging, and Prevention of Waste of Groundwater and Control of Subsidence in the Management Area TWDB has not developed guidance on how to approach this factor. It is up to the wishes of the GCD s on how they wish to approach it, whether in a qualitative, quantitative, or combination manner. But, the GCDs need to include stakeholder input so that this factor can be satisfactory addressed. Participation by the project team at town hall meetings or with individual GCDs is not included in the scope of this work. GCD management plans will be used to complete this requirement.

Each GCD must hold a public meeting within 90 days after the GMA approves its DFCs. During this meeting, the GCD needs to document stakeholder input regarding whether the DFCs provide a balance between the highest practicable level of groundwater production and the conservation, preservation, protection, recharging, and prevention of waste of groundwater and control of subsidence in the management area. This input is to be submitted by a report from the GCD to the GMA within 90 days after the GMA approves its DFCs.

15. References

Allen, S. 2013. Estimated historical water use and 2012 State Water Plan datasets: Kinney County Groundwater Conservation District. Texas Water Development Board. Groundwater Resources Division. Groundwater Technical Assistance Section.

Hutchison, W.R. 2011. GAM Task 10-027 (revised): Texas Water Development Board, GAM Task 10-027 Report. 8 p.

Hutchison, W.R., J. Shi, and M. Jigmond. 2011. Groundwater Flow Model of the Kinney County Area, Texas Water Development Board. 138 p.

Jones, I.C., J. Shi, and R. Bradley. 2013. GAM Task 13-033: Total estimated recoverable storage for aquifers in Groundwater Management Area 10.

Kinney County Groundwater Conservation District. 2013. Kinney County Groundwater Conservation District Groundwater Management Plan.

Plateau Region Water Planning Group. 2015. Plateau Region Initially Prepared Water Plan.

Shi, J. 2012. GAM Task Report 12-002: Modeled Available Groundwater in Kinney County (July 24, 2012).

Shi, J., C. Ridgeway, and L. French. 2012. Draft GAM Task Report 12-002: Modeled Available Groundwater in Kinney County (April 11, 2012).

Shi, J. and S. Wade. 2013. GAM Run 12-014: Kinney County Groundwater Conservation District Management Plan. 11 p.

Stoeser, D.B., N. Shock, G.N. Green, G.M. Dumonceaux, and W.D. Heran. 2005. A Digital Geologic Map Database for the State of Texas: U.S. Geological Survey Data Series 170.

U.S. Geological Survey. 2005. Preliminary integrated geologic map databases for the United States: Central states: Montana, Wyoming, Colorado, New Mexico, North Dakota, South Dakota, Nebraska, Kansas, Oklahoma, Texas, Iowa, Missouri, Arkansas, and Louisiana. GS Open-File Report 2005-1351. http://pubs.usgs.gov/of/2005/1351/.

16